# Gessco™ 162\*

## **Product Data Sheet**



Product Type | Liquid alkalinity builder

**Description** | Sodium hydroxide-based alkalinity builder to maintain higher pH levels

**Dosage** Will vary greatly depending on equipment type, operating pressure and feedwater characteristics. Consult your Gessco™ representative or

Service Technician for your situation.

**Principal Users** | Boilers operating up to 900 psi

**Features** 1) Most concentrated alkalinity builder available

2) Contains no carbonates to break down into CO2 and acidity

3) Approved by FDA for uses where steam contacts food.

### Characteristics

Physical form	Clear, colorless liquid
Density at 25C	1.51 (12.6 lbs/gal)
pH of product	13.0
Boiling Point	215°F (102°C)
Flash Point	Not flammable
Solubility	Completely water soluble

#### **Precautions**

Avoid inhalation of mists and contact with skin and eyes. Do not take internally. Keep from freezing. Keep out of reach of children. Goggles recommended when handling. Consult MSDS before handling.

#### **Packaging**

The fourth digit of the product number designates the container size:

Gessco<sup>™</sup> 162-1 - 5 gallon polyethylene pail Gessco<sup>™</sup> 162-2 - 30 gallon polyethylene drum Gessco<sup>™</sup> 162-3 - 55 gallon polyethylene drum

Robert Normand, Division Manager Ashley Clement, Inside Sales Coordinator

Phone: (504) 602-1821 Phone: (504) 602-1871 Email: <a href="mailto:robertn@gulfengr.com">robertn@gulfengr.com</a> email: <a href="mailto:ashleyc@gulfengr.com">ashleyc@gulfengr.com</a>

Gulf Engineering Co. LLC 611 Hill Street P.O.Box 10067 Jefferson, LA 70181-0067

Toll Free: (800) 347-4749 FAX: (504) 734-0765