


Gessco™ 650*

Biodegradable Descaler

Product Data Sheet



Product Type	Citric acid descaler									
Description	Solid citric acid descaler and cleaner									
Dosage	4 – 5 oz (about ½ cup) Gessco™ 650 Biodegradable Descaler for each gallon of water in the system; 100 lbs treats 340 – 400 gal of system capacity									
Principal Users	Evaporators, cooling towers, heat exchangers									
Features	<ol style="list-style-type: none"> 1. Removes calcium carbonate and other hardness mineral scales 2. Completely biodegradable 3. Low-foaming formulation 4. Each pound of Gessco™ 650 Biodegradable Descaler removes about 0.44 pounds of calcium carbonate 5. Safe for mild steel, stainless steels, galvanized steel, aluminum, brass, bronze, and all seal and gasket elastomers 6. Does not need heating during cleaning, but works faster at elevated temperatures 									
Directions	Add the calculated amount of Gessco™ 650 to clean water in the system through available openings. Circulate 8 – 12 hrs. Drain and rinse to remove loose material and excess cleaning product.									
Characteristics	<table border="1"> <tr> <td>Physical form</td> <td>White granular solid</td> </tr> <tr> <td>Density at 25C</td> <td>1.5 (95 lbs/ft³)</td> </tr> <tr> <td>pH (1% solution)</td> <td>2.2</td> </tr> <tr> <td>Solubility</td> <td>About 60g / 100 mL water</td> </tr> </table>		Physical form	White granular solid	Density at 25C	1.5 (95 lbs/ft ³)	pH (1% solution)	2.2	Solubility	About 60g / 100 mL water
Physical form	White granular solid									
Density at 25C	1.5 (95 lbs/ft ³)									
pH (1% solution)	2.2									
Solubility	About 60g / 100 mL water									
Precautions	Avoid contact with skin and eyes. Do not take internally. Keep from freezing. Keep out of reach of children. Goggles recommended when handling. Do not inhale dust. Consult MSDS before handling.									
Packaging	The fourth digit of the product number designates the container size: Gessco™ 650-4 - 100 lbs in a 10.5 gal fiber keg									

Gulf Engineering Co. LLC
 611 Hill Street
 P.O.Box 10067
 Jefferson, LA 70181-0067

email: insidesales@gulfengineering.com

Toll Free: (800) 347-4749 FAX: (504) 734-0765